

<http://salesforce.centralfreight.com/CFLPickUp/service.asmx>

More Examples at the bottom of the page to help with the codes.

Tables with codes used in the xml on this help page.

<http://salesforce.centralfreight.com/CFLPickUp/CFLPickupServiceCodesHelp.aspx>

<http://salesforce.centralfreight.com/CFLPickUp/service.asmx?WSDL>

<http://salesforce.centralfreight.com/CFLPickUp/service.asmx?op=getPickup>

<http://salesforce.centralfreight.com/CFLPickUp/CFLPickupServiceCodesHelp.aspx>

There is also a test HELLOWORLD web service to check for a connection. It will return a string.

<http://salesforce.centralfreight.com/CFLPickUp/service.asmx?op>HelloWorld>

```
<?xml version="1.0" encoding="utf-16"?>
<PickUp xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <ReturnCode xmlns="http://www.centralfreight.com/">0</ReturnCode>
  <Message xmlns="http://www.centralfreight.com/">1</Message>
  <UserName xmlns="http://www.centralfreight.com/">userName</UserName>
  <Password xmlns="http://www.centralfreight.com/">Password</Password>
  <QuickPickNumber xmlns="http://www.centralfreight.com/">1</QuickPickNumber>
  <ShipperCustomerNumber xmlns="http://www.centralfreight.com/">4399198001</ShipperCustomerNumber>
  <ShipperName xmlns="http://www.centralfreight.com/">Peter Gibbons</ShipperName>
  <ShipperAddress xmlns="http://www.centralfreight.com/">5601 W. Waco Drive</ShipperAddress>
  <ShipperCity xmlns="http://www.centralfreight.com/">Waco</ShipperCity>
  <ShipperState xmlns="http://www.centralfreight.com/">TX</ShipperState>
  <ShipperZip xmlns="http://www.centralfreight.com/">76710</ShipperZip>
  <ShipperPhone xmlns="http://www.centralfreight.com/">(254) 772-2120</ShipperPhone>
  <ShipperExtension xmlns="http://www.centralfreight.com/">4302</ShipperExtension>
  <ConsigneeName xmlns="http://www.centralfreight.com/">Brittney Gibbons</ConsigneeName>
  <ConsigneeAddress xmlns="http://www.centralfreight.com/">5601 W. Waco Drive</ConsigneeAddress>
  <ConsigneeCity xmlns="http://www.centralfreight.com/">Waco</ConsigneeCity>
  <ConsigneeState xmlns="http://www.centralfreight.com/">TX</ConsigneeState>
  <ConsigneeZip xmlns="http://www.centralfreight.com/">76710</ConsigneeZip>
  <ConsigneePhone xmlns="http://www.centralfreight.com/">(254) 772-2120</ConsigneePhone>
  <ConsigneeExtension xmlns="http://www.centralfreight.com/">4302</ConsigneeExtension>
  <ThirdPartyName xmlns="http://www.centralfreight.com/">21</ThirdPartyName>
  <ThirdPartyAddress xmlns="http://www.centralfreight.com/">23</ThirdPartyAddress>
  <ThirdPartyCity xmlns="http://www.centralfreight.com/">24</ThirdPartyCity>
  <ThirdPartyState xmlns="http://www.centralfreight.com/">25</ThirdPartyState>
  <ThirdPartyZip xmlns="http://www.centralfreight.com/">26</ThirdPartyZip>
  <ThirdPartyPhone xmlns="http://www.centralfreight.com/">27</ThirdPartyPhone>
  <ThirdPartyExtension xmlns="http://www.centralfreight.com/">28</ThirdPartyExtension>
  <DeliveryTypeID xmlns="http://www.centralfreight.com/">1</DeliveryTypeID>
  <ShipmentTerms xmlns="http://www.centralfreight.com/">Prepaid</ShipmentTerms>
  <PickupDateMMDDYYYY xmlns="http://www.centralfreight.com/">9/25/2013</PickupDateMMDDYYYY>
  <ReadyTime_HHMM xmlns="http://www.centralfreight.com/">800</ReadyTime_HHMM>
  <CloseTime_HHMM xmlns="http://www.centralfreight.com/">2359</CloseTime_HHMM>
  <TransactionType xmlns="http://www.centralfreight.com/">New</TransactionType>
  < BOL xmlns="http://www.centralfreight.com/">Bol Number</BOL>
  < PO xmlns="http://www.centralfreight.com/">PoNumber</PO>
  < PickupName xmlns="http://www.centralfreight.com/">Pickup Name</PickupName>
  < PickupPhone xmlns="http://www.centralfreight.com/">Pickup Number</PickupPhone>
  < ConfirmationEmail xmlns="http://www.centralfreight.com/">bblack@centralfreight.com</ConfirmationEmail>
  < Notes xmlns="http://www.centralfreight.com/">Notes</Notes>
  < CollAtPckup_TrueFalse xmlns="http://www.centralfreight.com/">True</CollAtPckup_TrueFalse>
  < Stackable xmlns="http://www.centralfreight.com/">False</Stackable>
```

```
<Weight xmlns="http://www.centralfreight.com/">10</Weight>
<Units xmlns="http://www.centralfreight.com/">1</Units>
<Hazmat xmlns="http://www.centralfreight.com/">True</Hazmat>
<FreightDescription xmlns="http://www.centralfreight.com/">46</FreightDescription>
<LiftGate xmlns="http://www.centralfreight.com/">1</LiftGate>
<HandlingUnitID xmlns="http://www.centralfreight.com/">13</HandlingUnitID>
<Test xmlns="http://www.centralfreight.com/">Test</Test>
<ReferenceID xmlns="http://www.centralfreight.com/">ReferenceID</ReferenceID>
</PickUp>
```

This will explain all tags in the XML and show the required and optional tags.

```
<ReturnCode >0</ReturnCode>
A return code of 0 = successful . This is output only
<Message xmlns="http://www.centralfreight.com/">1</Message>
Message tag are for Output only. These will help with error messages
```

```
<UserName xmlns="http://www.centralfreight.com/">userName</UserName>
user name is the Central Freight Lines eCentral account name
```

```
<Password xmlns="http://www.centralfreight.com/">password</Password>
password is the Central Freight Lines eCentral password
```

```
<QuickPickNumber xmlns="http://www.centralfreight.com/">1</QuickPickNumber>
this is an integer used on updates and cancels only. This lets us know the pickupnumber you would like to change
```

```
<ShipperCustomerNumber xmlns="http://www.centralfreight.com/">1</ShipperCustomerNumber>
Optional number. This is your central freight account number
```

```
<ShipperName xmlns="http://www.centralfreight.com/">Peter Gibbons</ShipperName>
<ShipperAddress xmlns="http://www.centralfreight.com/">5601 W. Waco Drive</ShipperAddress>
<ShipperCity xmlns="http://www.centralfreight.com/">Waco</ShipperCity>
<ShipperState xmlns="http://www.centralfreight.com/">TX</ShipperState>
<ShipperZip xmlns="http://www.centralfreight.com/">76710</ShipperZip>
<ShipperPhone xmlns="http://www.centralfreight.com/">(254) 772-2120</ShipperPhone>
<ShipperExtension xmlns="http://www.centralfreight.com/">4302</ShipperExtension>
<ConsigneeName xmlns="http://www.centralfreight.com/">Brittney Gibbons</ConsigneeName>
<ConsigneeAddress xmlns="http://www.centralfreight.com/">5601 W. Waco Drive</ConsigneeAddress>
<ConsigneeCity xmlns="http://www.centralfreight.com/">Waco</ConsigneeCity>
<ConsigneeState xmlns="http://www.centralfreight.com/">TX</ConsigneeState>
<ConsigneeZip xmlns="http://www.centralfreight.com/">76710</ConsigneeZip>
<ConsigneePhone xmlns="http://www.centralfreight.com/">(254) 772-2120</ConsigneePhone>
<ConsigneeExtension xmlns="http://www.centralfreight.com/">4302</ConsigneeExtension>
<ThirdPartyName xmlns="http://www.centralfreight.com/">21</ThirdPartyName>
<ThirdPartyAddress xmlns="http://www.centralfreight.com/">23</ThirdPartyAddress>
<ThirdPartyCity xmlns="http://www.centralfreight.com/">24</ThirdPartyCity>
<ThirdPartyState xmlns="http://www.centralfreight.com/">25</ThirdPartyState>
<ThirdPartyZip xmlns="http://www.centralfreight.com/">26</ThirdPartyZip>
<ThirdPartyPhone xmlns="http://www.centralfreight.com/">27</ThirdPartyPhone>
<ThirdPartyExtension xmlns="http://www.centralfreight.com/">28</ThirdPartyExtension>
```

```
<DeliveryTypeID xmlns="http://www.centralfreight.com/">1</DeliveryTypeID>
```

zero for standard delivery. The table on this web page

<http://salesforce.centralfreight.com/CFLPickUp/CFLPickupServiceCodesHelp.aspx> are the valid delivery

types.

<ShipmentTerms xmlns="<http://www.centralfreight.com/>">Prepaid</ShipmentTerms>
the shipment terms are Prepaid,Collect,Thirdparty

<PickupDateMMDDYYYY xmlns="<http://www.centralfreight.com/>">9/25/2013</PickupDateMMDDYYYY>
Slashes are required. This is the date freight is ready to pick up

<ReadyTime_HHMM xmlns="<http://www.centralfreight.com/>">800</ReadyTime_HHMM>
NO Colon in time. This is the time the freight is ready for pick up

<CloseTime_HHMM xmlns="<http://www.centralfreight.com/>">2359</CloseTime_HHMM>
NO Colon in time. This is the when the freight can no longer be picked up.

<TransactionType xmlns="<http://www.centralfreight.com/>">New</TransactionType>
required. Transactions are New,Change, Cancel. When using Change and Cancel a quickpick number is also required.

<BOL xmlns="<http://www.centralfreight.com/>">Bol Number</BOL>
optional bill of lading number

<PO xmlns="<http://www.centralfreight.com/>">PoNumber</PO>
optional po number

<PickupName xmlns="<http://www.centralfreight.com/>">Pickup Name</PickupName>
Contact name for pickup

<PickupPhone xmlns="<http://www.centralfreight.com/>">Pickup Number</PickupPhone>
contact phone number for pickups

<ConfirmationEmail xmlns="<http://www.centralfreight.com/>">bblack@centralfreight.com</ConfirmationEmail>
email used after pickup is completed.

<Notes xmlns="<http://www.centralfreight.com/>">Notes</Notes>
any extra notes to pass through to central

<CollAtPckup_TrueFalse xmlns="<http://www.centralfreight.com/>">True</CollAtPckup_TrueFalse>
This is true or false option does the driver collect money at pickup

<Stackable xmlns="<http://www.centralfreight.com/>">False</Stackable>
true or false option. Is freight stackable

<Weight xmlns="<http://www.centralfreight.com/>">10</Weight>
integer use for weight in pounds

<Units xmlns="<http://www.centralfreight.com/>">1</Units>
number of units to pick up

<Hazmat xmlns="<http://www.centralfreight.com/>">True</Hazmat>
True or false option. This will show the freight is hazardous

<FreightDescription xmlns="<http://www.centralfreight.com/>">Dog Food</FreightDescription>
optional description of the freight

<LiftGate xmlns="<http://www.centralfreight.com/>">1</LiftGate>
optional field 1 for true or zero for false.. This will send a lift gate when freight is picked up

<HandlingUnitID xmlns="<http://www.centralfreight.com/>">10</HandlingUnitID>
used to for the handling unit. 10 is default for pallets.

<http://salesforce.centralfreight.com/CFLPickUp/CFLPickupServiceCodesHelp.aspx> are the valid handling unit id.

<Test xmlns="<http://www.centralfreight.com/>">Test</Test>

This will validate everything and try insert data into a test environment. All web service request will go to a test unless the user id is in production mode. You may use test at any time by entering test in this field

<ReferenceID xmlns="<http://www.centralfreight.com/>">ReferenceID</ReferenceID>

This is a customer reference id. Used by the customer.
</PickUp>

General Return Code Errors

ReturnCode = "101095"
Not Logged In correctly"
ReturnCode = "101995"
Incorrect Login or Password
ReturnCode = "109095"
Lane not serviced from shipper zip to consignee zip

ReturnCode = "108095"
Invalid pickup date
ReturnCode = "108085"
Dates must contain slashes
ReturnCode = "108080"
Invalid Close Time
ReturnCode = "108060"
Current Shipper Time past cut off time

ReturnCode = "106050"
Error Invalid Shipment Terms.. Please only use PREPAID COLLECT THIRDPARTY

ReturnCode = "031195"
Error Invalid Pickup Number. Pickup number required to change or cancel a pickup

ReturnCode= 101010
'Error Transaction type'
Only these are valid options 'NEW' , 'CHANGE' , 'CANCEL'

ReturnCode = 101011
'Error Catch Transaction Type'
this is just a generic transaction type error.

ReturnCode= 101012
'Error Transaction type'
Only these are valid options 'NEW' , 'CHANGE' , 'CANCEL'

ReturnCode = "951003"

Error Invalid Unit amount.. Please only use positive whole numbers

ReturnCode = "951010"

Error Invalid Hazmat Entry.. Please only use True OR False

ReturnCode = "959595"

Error Invalid Data.

ReturnCode = "031095"

Error Invalid Required Data not provided.